# JN6204 & JN6208

AHD 1080P DVR




## FC (E

### Features

- AHD & IP Hybrid Design
- Max. recording resolution:
  1920 x 1080p
- H.264 video compression
- 1 internal SATA HDD
- · HDMI/VGA video outputs
- Video extraction through network or using USB flash drive
- Video management software with sureSIGHT
- Supporting sureLINK for dynamic IP Internet connection
- iView HD for remote monitoring on mobile phones

#### **Dimensions**

#### Unit: mm



### **Specifications**

MODEL		JN6204	JN6208	
VIDEO INPUT	ANALOG CAMERA		AHD (1080p), AHD (720p), PAL, NTSC	
	NO. OF CHANNEL		4	8
	IP CAMERA		TeleEye MP, MQ Series	
	NO. OF CHANNEL		1	4
VIDEO OUTPUT	MAIN	DIGITAL VIDEO	1 channel, 1920 x 1080	
		VGA	1 channel, 1920 x 1080	
RECORDING	MODE		Manual, schedule, motion, event-driven	
	HD TYPE		SATA X 1	
	MAX. RECORDING RATE PER CHANNEL		1080p: 12 / 15fps 720p: 25 / 30fps	3MP: 6 / 7 fps 1080p: 12 / 15fps 720p: 25 / 30fps
	PLAYBACK		Play, Forward, Backward, Pause, Digital Zoom	
COMMUNICATION	NETWORK		RJ-45, 10/100 base-T ethernet (auto-sensing)	
	CONCURRENT USER		10	
	WEB SERVER		Built-in	
	TELEMETRY CONTROL		RS 485	
	USB		USB2.0 x 2	
AUDIO	INPUT		RCA X 4	
	OUTPUT		RCA X 1	
	IP CAMERA AUDIO INPUT		1	4
EVENT HANDLING	EVENT TYPE		Video motion detection, External alarm, Video loss	
	ACTION TYPE		Local recording, email notification, telemetry preset	
	EXTERNAL ALARM INPUTS		4	
	IP CAMERA ALARM INPUT		1	4
RELAY SWITCH	NO. OF CHANNEL		1	
POWER	VOLTAGE		12V DC	
	MAX. RATING		16W	18W
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE		-10°C - 50°C	
	RELATIVE HUMIDITY		10% - 90%	
MECHANICAL DESIGN	DIMENSION (mm)		300 (W) x 255 (D) x 58 (H)	
	WEIGHT (kg)		1.25	

www.TeleEye.com

TeleEye Group

DISTRIBUTED BY:

Hong Kong Bangladesh China Malaysia Philippines South Africa Sri Lanka Turkey U.K.